

SIC600N

NEW!!! 1/2" Miniature Color Machine Vision Camera Replaces: SIC400N & IV-CCAM2 (as of March 2013)







IVS Imaging introduces the new upgraded & easier to use Costar SIC600N. The SIC600N is replacing the older ½" models from Costar & Industrial Vision Source. With the new Sony Effio chipset, upgraded materials & an OSD that we designed from customer feedback, the SIC600N is sure to impress for years to come.


IVS Imaging is Your Single Source for machine vision products so don't forget to order lenses, cables, monitors, filters & power supplies.


- Sony Effio ½" CCD Sensor
- 410,000 Pixels @ 768(H)x494(V) NTSC & 752(H)x582(V) PAL
- 540TVL (470TVL = SIC400N)
- High Sensitivity 0.05Lux at F1.2, 50IRE
- Multi-Zone Backlight Compensation
- S-Video & Composite (BNC) outputs
- Electronic Shutter 1/60(1/50) to 1/100,000 sec.
- Variable Gamma
- Multi-mode White Balance: ATW/AWC/Push/Manual/2 Presets
- OSD Menu & Adjustment
- Auto Iris DC Lens Connection

101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6810 • Fax: 469-635-6822 • Toll Free: 1-888-446-1301

SIC600N Specifications

Sensor	½" Sony IT CCD
Effective Pixels	768(H) x 494(V)
Horizontal Resolution	540TVL
Video Outputs	Composite video
	(1Vp-p, 75Ω, unbalanced)
	Separated Y/C Signal (Y;1Vp-p/75Ω, C;0.286Vp-p/75Ω)
Sync System	Internal
Video S/N Ratio	48db (AGC off)
Min. Illumination	0.05lux @ F1.2, 50 IRE
White Balance	2400K - 10,000K
Shutter Speed Range	1/60 (1/50) – 1/100,000sec
Auto Iris Lens	DC Type: Coupling coil impedance
Gamma Correction	Variable
OSD Functions/Adjustments:	Motion Detection
	Day/Night
	Sync
	Back Light Compensation
	Privacy
	Motion Detection
	Noise Reduction
	Picture Adjust
	OSD Languages
Lens Mount	C/CS Mount
Power	DC12V / 2.5 Watt
Operating Temp	-10C to +50C (14 to 122 F)
Weight	140g (0.31lbs)
Dimensions (w/o lens)	41(w)x41(h)x51.6(d) mm
Supplied Accessories	Lens Cap, C-mount adapter & manual







Setup menu







